

**REMARKS:**

The specification and claims of the referenced application have been amended in accordance with common U.S. Patent Practice and to remove the multiple dependencies of claims. New Claims 14-26 were added. No new matter has been introduced through the foregoing amendments. Entry is in order.

To the extent necessary, a petition for an extension of time under 37 C.F.R. 1.136 is hereby made. Please charge any shortage in fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account 07-1337 and please credit any excess fees to such deposit account.

Respectfully submitted,

**LOWE HAUPTMAN & BERNER, LLP**



Kenneth M. Berner

Registration No. 37,093

1700 Diagonal Road, Suite 310  
Alexandria, Virginia 22314  
(703) 684-1111 KMB/iy  
Facsimile: (703) 518-5499  
**Date: September 30, 2005**

**Method of processing signals, and active sonar  
implementing same**

**Field of the invention**

5

The invention relates to the field of underwater acoustics and more particularly to the field of signal processing in a low frequency (LF) active sonar system.

10 **Background of the invention**

This type of system is generally towed from a surface vessel and comprises a fish equipped with an LF emitter which tows a linear receiving antenna furnished with  
15 acoustic or hydrophonic sensors. Such a fish and such an emitter are for example described respectively in French Patents published under numbers 2735645 and 2776161. However, the invention may be applied to all types of active sonars. It is well known that an active  
20 sonar emits recurrent acoustic pulses and that the echoes received in return are processed to detect and classify any targets.

When an active sonar operates in a zone such that the  
25 bottom is insonified, the reverberation which originates from the bottom in essence greatly limits the operational usefulness of the sonar on account of the overly large number of false alarms which appear. This is particularly true for shallow depths.

30

To reduce nuisance in a reverberating medium, it is known to use emission codes that harness the wide frequency bands, typically an octave, of present-day transducers. These codes possess good distance  
35 resolution, hence the large number of alarms that are produced.

It is known to emit at each recurrence, either an HFM (Hyperbolic Frequency Modulation) code, or a BPSK (Binary Pulse Shift Keying) code or an FP (Frequency Pulse) code.

5

The HFM code is Doppler tolerant: it therefore does not allow measurement of the Doppler induced by a target in motion but, on the other hand, the matched filtering on reception requires only a single copy.

10

The BPSK code is Doppler intolerant and is used to measure the Doppler; it allows the same detection performance as the HFM code but the matched filtering on reception requires a significant number of copies to carry out the matched filtering on reception, typically a number greater than 200, and hence a correspondingly large processing cost.

15

### **Object of the invention**

20

As for the FP code, it is used to measure the inherent Doppler of the emitter.

### **Summary of the invention**

25

The present invention makes it possible to decrease the false alarm rate while retaining the classification of the objects.

30

The object of the invention is therefore a method of processing signals received corresponding to a signal emitted comprising by recurrence two pulses, a first Doppler tolerant broadband pulse and a second Doppler intolerant broadband pulse, comprising:

35

- a step of detecting objects performed on the part of the signal received corresponding to the first pulses and providing an alarm for each object detected, and

- a step of classifying the objects detected performed on the part of the signal received corresponding to the second pulses for the alarms satisfying at least one predetermined criterion.

5

At each recurrence, the two HFM and BPSK codes are emitted. The detection of the alarms is done with the HFM code and the estimation of the Doppler is done with the BPSK code on the alarms which exceed a certain

10 threshold, so as to eliminate the bottom echoes. Stated otherwise:

- detection with the HFM code
- Doppler classification with the BPSK code.

15 Moreover, the bottom echoes being identified, the measurement of the inherent Doppler of the emitter is done by analyzing the bottom echoes produced by the BPSK code.

## 20 **Description of the figures**

The characteristics and advantages of the invention will become more clearly apparent on reading the description, offered by way of example, and the figures

25 pertaining thereto which represent:

- Figure 1, the successive steps of the method according to the invention,
  - Figure 2, the probability distributions of the
- 30 measured Doppler  $d_m$  for two hypotheses:  $H_0$  for (stationary) bottom echo and  $H_1$  for assumed true Doppler echo  $d_i$ .

## **Detailed Description**

35

Figure 1 represents the successive steps of the method according to the invention.

In a known manner, the hydrophone signals undergo upstream processing (demodulation, filtering, amplification, etc.) and are then digitized. In the case of an active sonar, these signals contain the signals emitted after propagation through the water via the direct path and the reflected paths to which are added the reverberated signals. In particular, among the signals reflected, the echoes originating from the sea bottom constitute a significant source of false alarms, in particular at shallow depths.

According to the invention, at each recurrence are emitted two coded pulses, HFM and BPSK, whose characteristics make it possible to separate them on reception. They can be emitted at different instants with totally or partly overlapping frequency bands, or else be emitted simultaneously in distinct frequency bands, or both at once.

Referring to Figure 1, the processing of the hydrophone signals consists firstly in forming channels S1 in a known manner, this processing being independent of the code emitted.

To the signals of HFM channels is applied the matched filtering processing S2 consisting in correlating the signal received with a copy of the signal emitted which after rms detection provides signals representative of the energy as a function of channel (v) and of time (t) i.e.  $E_{HFM}(v, t)$ .

The next step S3 consists in detecting and in sorting the alarms with regard to an energy criterion. In a conventional manner, the local maxima are firstly searched for by comparison with a predetermined threshold. Thereafter, a normalization is performed by calculating for each local maximum a value equal to  $(E_{HFM} - M) / \sigma$  where M is the mean of the reference noise, taken in the neighborhood of the "channels/time" space

(v,t) and  $\sigma$  the corresponding standard deviation. Then, any maxima around each maximum are eliminated if they have lower normed energy. Finally, the actual detection is obtained by comparing the noneliminated maxima with a normed energy threshold.

According to the invention, the matched filtering processing S5 on the "BPSK" channel signals is performed only on the alarms arising from the processing of the HFM pulses S4. The matched filtering processing corresponding to the BPSK code which is Doppler tolerant requires that the channel signal be correlated with several Dopplerized copies covering a range of given target velocities. Thus for an alarm are obtained as many signals as there are copies and form the Doppler channels.

The next step S6 consists in estimating the Doppler  $d$  and the associated standard deviation  $\sigma_{d_i}$  of the alarm "i" on the basis of the signals arising from the Doppler channels. If  $d_{\text{channel}}$  is the Doppler given by the channel in which the alarm is to be found, the Doppler  $d$  is obtained by interpolation with the Dopplers of the adjacent channels.

The next step S7 consists in estimating the inherent Doppler  $d_p$  due to the velocity of the antennas, emission and reception, with respect to the bottom. It is estimated at each instant, either on the basis of a Doppler of the echoes originating from the bottom and detected by the BPSK code, or on the basis of the reverberation spectrum obtained by an FP code emitted with the HFM and BPSK codes. The standard deviation  $\sigma_d$  is also estimated.

The next step S8 consists in deciding whether this alarm corresponds to a bottom echo or indeed to a true echo at non zero radial velocity. The values of the

Doppler  $d_i$  and of the inherent Doppler  $d_p$  and also the corresponding rms deviations  $\sigma_{d_i}$  and  $\sigma_{d_p}$  are available.

5 Represented in Figure 2 are the probability distributions of the measured Doppler  $d_m$  for two hypotheses:  $H_0$  for (stationary) bottom echo and  $H_1$  for assumed true Doppler echo  $d_i$ .  $H_0$  is centered on  $d_p$  with a rms deviation  $(\sigma_{d_p}^2 + \sigma_{d_p}^2)^{1/2}$  and  $H_1$  is centered on  $d_i$  with a rms deviation  $\sigma_{d_i}$ .

10 To decide,  $d_i - d_p$  is calculated and a threshold  $S$  is chosen: if  $d_i - d_p > S$ , there is a true echo. The value of  $S$  is obtained on the basis of the values of  $P_f$  which is the probability of deciding wrongly that a bottom echo  
15 is true.

The process of discrimination between true echo with non zero radial velocity and bottom echo for each alarm detected by HFM is repeated. Next, among the HFM alarms  
20 detected and sorted, one undertakes the elimination S9 of the alarms which correspond to the bottom echoes (or to true echoes with zero radial velocity).

In step S10 is obtained an image of the tracks (series  
25 of alarms as a function of time and direction) which is ridded of the false alarms and in particular the bottom echoes, all the better when they are strong and hence a nuisance.

## **ABSTRACT**

### **Method of processing signals, and active sonar implementing same**

The invention relates to the field of underwater acoustics and more particularly to the field of signal processing in a low frequency (LF) active sonar system.

The present invention makes it possible to decrease the false alarm rate while retaining the classification of the objects.

The subject of the invention is a method of processing signals received corresponding to a signal emitted comprising by recurrence two pulses, a first Doppler tolerant broadband pulse of HFM type in particular and a second Doppler intolerant broadband pulse of BPSK type in particular, comprising:

- a step of detecting objects performed on the part of the signal received corresponding to the first pulses and providing an alarm for each object detected, and
- a step of classifying the objects detected performed on the part of the signal received corresponding to the second pulses for the alarms satisfying at least one predetermined criterion.

(Figure 1)